

Permatex, Inc.
10 Columbus Blvd.
Hartford, CT 06106 USA
Telephone: 1-87-Permatex
(877) 376-2839
Emergency: 800-255-3924
International Emergency: +01-813-248-0585

Material Safety Data Sheet

1. PRODUCT IDENTIFICATION

Product Name: DIELECTRIC TUNE-UP GREASE 3 OZ
Item No: 22058
Product Type: Lubricant

2. COMPOSITION/INFORMATION ON INGREDIENTS

| Component | Weight% | ACGIH; TLV-TWA | OSHA PEL |
|---|---------|----------------|------------|
| POLYDIMETHYLSILOXANE 63148-62-9 | >70 | Not listed | Not listed |
| MODIFIED SILICON DIOXIDE 68611-44-9 | <10 | Not listed | Not listed |
| OXIRANE, METHYL-, POLYMER 52624-57-4 | 0.5-5.0 | Not listed | Not listed |

3. HAZARDS IDENTIFICATION

Toxicity: May cause eye and skin irritation. Note: This product does not contain microcrystalline silica.
Primary Routes of Entry: Eye and skin contact, ingestion, inhalation
Signs and Symptoms of Exposure: Overexposure may cause eye and skin redness.
Medical Conditions Recognized as Being Aggravated by Exposure: None known.

4. FIRST AID MEASURES

Ingestion: If swallowed, DO NOT induce vomiting. Keep individual calm. Obtain medical attention.
Inhalation: Move to fresh air in case of accidental inhalation of vapours.
Skin Contact: Wash off with soap and water. If skin irritation persists, call a physician.
Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

5. FIRE FIGHTING MEASURES

Flash Point °F(C°): >200°F TCC
Recommended Extinguishing Media: Carbon Dioxide, Dry Chemicals, Foam.
Special Fire-Fighting Procedures: No special procedures.
Hazardous Products of Combustion: Oxides of carbon, Oxides of silicon, Formaldehyde
Unusual Fire/Explosion Hazards: None.
Lower Explosive Limit: Not determined
Upper Explosive Limit: Not determined

6. ACCIDENTAL RELEASE MEASURES

Spill Procedures: Maintain good ventilation. Take up with an inert absorbent. Store in a closed waste container until disposal. Clean up spills thoroughly as residue is slippery.

7. HANDLING AND STORAGE

Storage: Store below 100°F.
Handling: Avoid prolonged skin contact. Keep away from eyes.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Eyes: Safety glasses.
Skin: Neoprene or nitrile gloves recommended.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ventilation: General; local exhaust ventilation as necessary to control any air contaminants to within their exposure limits (or to the lowest feasible levels when limits have not been established) during the use of this product.
Respiratory Protection: Not required under normal use. In case of insufficient ventilation, wear suitable respiratory equipment.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance: White, translucent grease
Odor: Mild
Boiling Point: Not determined
pH: Does not apply
Solubility in Water: Nil
Specific Gravity: 1.0
VOC(Wt.%): 0
Vapor Pressure: Not determined
Vapor Density (Air=1): Heavier than air
Evaporation Rate: <1 (butyl acetate =)

10. STABILITY AND REACTIVITY

Chemical Stability: Stable at normal conditions
Hazardous Polymerization: Will not occur.
Incompatibilities: Acids, Strong oxidizers, Reducing agents
Conditions to Avoid: Heat.
Hazardous Products of Combustion: Oxides of carbon, Oxides of silicon, Formaldehyde

11. TOXICOLOGICAL INFORMATION

See Section 3

12. ECOLOGICAL INFORMATION

No data available

13. DISPOSAL CONSIDERATIONS

Recommended Method of Disposal: Disposal should be made in accordance with federal, state and local regulations.
US EPA Waste Number: NH - Not a RCRA Hazardous Waste Material

14. TRANSPORTATION INFORMATION

DOT (49CFR 172)

Ground Transport (DOT)

DOT Shipping Name: Not Regulated
Hazard Class: None
UN/ID Number: None

IATA

Proper Shipping Name: Not regulated
Class or Division: None
UN/ID Number: None

IMDG

Proper Shipping: Not regulated
Hazard Class: None
UN Number: None

Marine Pollutant: None

15. REGULATORY INFORMATION

SARA 313 Chemicals: The following component(s) is listed as a SARA Section 313 Toxic Chemical.

NONE

California Proposition 65: No California Prop 65 chemicals are known to be present at or above the No Significant Risk Level

TSCA Inventory Status: All components of this product are listed (or exempt) on the EPA TSCA inventory.

Product Name: DIELECTRIC TUNE-UP GREASE 3 OZ

Item No: 22058

16. OTHER INFORMATION

Estimated NFPA Rating: HEALTH 1, FLAMMABILITY 1, REACTIVITY 0.

Estimated HMIS Classification: HEALTH 1, FLAMMABILITY 1, PHYSICAL HAZARD 0

NFPA is a registered trademark of the National Fire Protection Assn.

HMIS is a registered trademark of the National Paint and Coatings Assn.

Prepared By: Denise Boyd, Manager-Environmental, Health & Safety
Company: Permatex, Inc. 10 Columbus Blvd. Hartford, CT USA 06106

Revision Date: March 05, 2010

Revision 2

Number:

Telephone No.: 1-87-Permatex (877) 376-2839